

INT - 3.21 **SM 65 95 70**

INTERNAL **AUTOMATED BLACKOUT SYSTEMS**

MOTORISED BLACKOUT ROLLER BLIND SYSTEMS

APPLICATION SM 65 95 70

The Helioscreen full blackout system is extremely versatile and is ideal for situations where a complete light block out is necessary like boardrooms and home theatres in both commercial and domestic applications. The system features stylish steel side channels with double internal brushes. This system is automated with a Somfy motor for the ultimate ease of use. The Warranty on the Helioscreen motorised Blackout system is 5-years.

SYSTEM SPECIFICATIONS SM 65 95 70

 MINIMUM
 WIDTH
 800mm

 MAXIMUM
 WIDTH
 3000mm

 MAXIMUM
 DROP
 3200mm



TECHNICAL INFORMATION SM 65 95 70

HEAD BOX• Side brackets press formed steel, pre-treated and powder coated

Bracket/head box projection 95mm
Head box to be custom powder coated

CONTROL END • Somfy motorised system

• Parts made with high strength fibreglass reinforced polyester

and high carbon steel

TUBE • 100% extruded aluminium

• 65mm outside diameter

• 2.0mm wall thickness

* 70mm x 26mm blackout aluminium side channels with

compressible blackout brush seal

• Side channels to be custom powder coated

• Comprises of an outside sleeve and centre shaft

• Roller rides on bearing surface

BASE BAR • 18mm x 35mm extruded aluminium base bar helio style with

compressible blackout brush seal

Custom powder coating

INTELLIGENT SUN CONTROL SOLUTIONS®









INT - 3.21 **SM 65 95 70**


2D DIAGRAM SM 65 95 70





COMPONENTRY SM 65 95 70

70mm HEADBOX END CAP



70mm SIDE CHANNEL



Helioscreen Australia Pty Ltd T +61 2 8426 1300 F +61 2 9453 0744

BASE BAR **SM 65 95 70**







